CERTIFICATE OF ANALYSIS

BASELINE® Nitric Acid

1A] F	PRODU	CT NUN	/IBER: \$	S02010 ²		LOT NUMBER: 1217050 AS					SSAY (HNO ₃ , w/w): 68%					
3 Li < 0.05	2A 4 Be < 0.05	average evaporate Nitric Acid	of three aliced to drynes d / 2% Hyd	quots subsass. The resurred	by high resonant plant by high residuration with the second part of the second plant by high residual plant by hig	n three sam e is reconst platile elem	nples repres ituted in a s ents (indica	sentative of mall volume ted by *), th	the lot. The of SEASTA ne acid sam	e samples a AR™ BASEL ples are dil	are slowly INE® 2% uted then	3A 5 B < 10	4A	5A	6A	7A	
< 1	< 1	•	ue is subtrac 4B		6B	7B	ine standan	8	or the blank	1B	2B	< 1					
19 K	20 Ca < 10	21 Sc < 0.01	22 Ti < 0.5	23 V < 0.01	24 Cr < 1	25 M n < 0.05		27 Co	28 Ni < 5	29 C u < 0.5	30 Zn < 0.5	31 Ga < 0.01	32 Ge < 0.05	33 As < 1	34 Se < 10		
37 Rb < 0.01	38 Sr < 0.05	39 Y < 0.05	40 Zr < 0.05	41 Nb < 0.05	42 Mo < 0.5	N.	44 Ru < 0.05	45 Rh < 0.01	46 Pd < 1	47 Ag < 0.01	48 C d < 0.05	49 In < 0.01	50 Sn < 0.5	51 Sb < 0.01	52 Te < 0.01		10
55 Cs < 0.01	56 Ba < 0.5	57 La < 0.05	72 Hf < 0.01	73 Ta < 0.01	74 W < 0.05	75 Re < 0.01			78 Pt < 1	79 Au < 1	80 Hg < 20	81 TI < 0.01	82 Pb < 0.05	83 Bi < 0.01			

ALL VALUES ARE REPORTED IN PARTS PER TRILLION (PPT)

(1) (2)	ı
(3)	ľ

(1) Atomic Number

(2) Elemental Symbol

(3) Concentration (mean in ppt)

(4) 1 Standard Deviation (N=3)

58 Ce	59 Pr	60 Nd		62 Sm	63 Eu	64 Gd	65 Tb	66 Dy	67 Ho	68 Er	69 Tm	70 Yb	71 Lu
< 0.05	< 0.01	< 0.01		< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
90 Th		92 U											
< 0.01	b)	< 0.01	1.5		_	200							
L 4	4												



HNO₃ (67 - 70%): Properties

Molar Mass: 63.01g/mol

Density: 1.41 g/ml Molarity: 16 moles/litre Normality: 16 moles/litre

Bry Gener

Greg Henson QA & RA Manager Release Date: June 02, 2017 Expiry Date: June 02, 2020





SEASTAR™'s Product Integrity Guidelines:

We have found our products, unopened and sealed, maintain the certified integrity, or product quality, for their stated certification period under the following conditions:

- Store at room temperature, maximum range 15°C (59°F) to 25°C (77°F).
- Avoid exposure to sunlight or ultraviolet light sources.
- Open in a 'particle free' environment. SEASTAR recommends a HEPA or ULPA particle filtered trace metal clean room. Open product should be handled under Class 100 or ISO 5 clean room or better conditions.

Once opened, product integrity will depend on proper handling and exposure to contaminants. To reduce trace metal contamination, the inner pack of plastic bags and bottle should be opened under Class 100 or ISO 5 clean room or better conditions to maintain the integrity of the product. The use of plastic gloves, hair net and a clean room suit is also advised.

Safety Guidelines:

PRIOR to opening or storing this product be sure to consult the Safety Data Sheet (SDS) to ensure safe storage and handling with regards to this hazardous material. This information must be read and understood prior to use or storage.

SAFETY HANDLING NOTES: Consult the SDS PRIOR to handling this product. Use proper safety apparel according to the recommendations of the SDS. Exposure controls and personal protection should include: a properly functioning fume hood, protection for eyes (safety glasses), hands (chemically compatible gloves), feet (chemically compatible boots), and exposed skin (splash protection and a chemically compatible apron). All of these items must conform to local/regional/national regulatory requirements.

Greg Henson

Breg denon-

QA & RA Manager

2061 Henry Avenue West, Sidney, BC, Canada V8L5Z6

Phone: 1-250-655-5880 Fax: 1-250-655-5888 Toll free: 1-800-663-2330 (North America only)

Email: seastar.technicalsupport@seastarchemicals.com

Web: www.seastarchemicals.com